



Rx POWER RANGES

Access the latest version online at www.Signetek.com

PLEASE REVIEW PROGRESSIVE AVAILABILITY GUIDES FOR LENS MATERIAL OFFERINGS.

Index	Material	KODAK Unique™, Unique DS™, Precise® PB /Short MonitorView™, DirecTek™ /Short	KODAK Precise/Short, KODAK Concise®, Navigator®/Short
		Add Range +0.75 to +3.50 in .25 D steps	Add Range +1.00 to +3.00 in .25 D steps
		Power Range	Power Range
1.50	Standard Resin	-8.00 to +4.00	-8.00 to +5.00
	Transitions®	-8.00 to +4.00	-8.00 to +5.00
	Transitions XTRActive™, Transitions Vantage™, PhotoViews™, Drivewear®	-8.00 to +4.00	
	Polarized	-6.75 to +4.00 DS -6.00 to +4.00	-7.00 to +5.00
1.53 Trivex®	Clear	-10.00 to +4.50	-9.00 to +5.00
	Transitions, Transitions Vantage	-10.00 to +4.50	
	Transitions XTRActive	-10.00 to +5.00	
	NXT® Tints, Mirrors, Photochromic	-9.00 to +5.00	
	NXT Polarized & NXT Photochromic Polarized	-7.00 to +5.00	
1.56	Clear, Blu-Tech HI Indoor	-10.00 to +5.00	-10.00 to +6.00
	SunSensors®	-10.00 to +5.00	-10.00 to +6.00
	Blu-Tech HI Outdoor	-8.00 to +5.00	
1.586 Poly	Clear	-10.00 to +5.00	-10.00 to +6.00
	Transitions, XTRActive, Vantage	-10.00 to +5.00	-10.00 to +6.00
	Life Rx™	-10.00 to +5.00	
	Polarized	-10.00 to +5.00	
1.60	Clear	-11.00 to +6.00	-11.00 to +7.00
	Transitions	-11.00 to +6.00	
	Polarized	-10.00 to +5.75	
1.67	Clear	-12.00 to +6.00	-12.50 to +7.00 C-12.50 to +5.00
	Transitions	-12.00 to +6.00	P-12.50 to +7.00
	Transitions XTRActive	-12.00 to +6.00	
	Polarized	-12.00 to +7.50	
1.74	Clear	-13.25 to +9.00	
	Transitions	-13.00 to +9.00	

All power ranges represent the max total power available including the cylinder power in minus cylinder form (-4.00 max cylinder power)

Index	Material	Add Range	Power Range
SINGLE VISION SPHERICAL			
1.50	Standard Resin		-8.00 to +6.00
	Polarized 1.50		-6.00 to +6.00
	Clear, Drivewear, PhotoViews, Transitions, Transitions XTRActive, Transitions Vantage		-8.00 to +6.00
1.53 Trivex	Clear, Transitions, Transitions XTRActive, Transitions Vantage		-10.00 to +6.00
	NXT Tints, Mirror, Photochromics		-9.00 to +6.00
	NXT Polarized, Photochromic Polarized		-7.00 to +6.00
1.56	Clear, SunSensors		-10.00 to +6.50
	Clear (aspheric)		-10.50 to +9.00
	BluTech High Impact Indoor		-10.00 to +6.00
	BluTech High Impact Outdoor		-8.00 to +6.00
1.586 Poly	Signia™ Clear (tintable)		-11.75 to +6.50
	Polarized, Transitions, Vantage		-10.00 to +6.50
	Transitions XTRActive		-11.00 to +6.75
	Life Rx		-10.00 to +8.00
1.60	Life Rx (aspheric)		-8.50 to +8.00
	Polarized		-10.00 to +7.00
1.67	Clear, Transitions		-11.50 to +7.50
	Clear		-12.00 to +8.00
1.67	Polarized, Transitions, Transitions XTRActive 1.67		-12.00 to +7.50
	Clear		-13.25 to +9.00
1.74	Transitions 1.74		-13.00 to +9.00
	Clear		-13.25 to +9.00
KODAK SINGLE VISION & KODAK FLAT-TOP 28 ASPHERIC			
1.56	Clear, SunSensors (SV & FT)	1.00 to 3.00	-10.50 to +9.00
1.586	Poly (SV only)		-8.50 to +8.00
FLAT-TOP 28 & 35			
1.50	Signia 1.50	1.00 to 3.00	-8.00 to +6.00
1.50	Polarized (FT-28 only)	1.00 to 3.00	-8.75 to +6.00
1.50	Transitions, PhotoViews (FT-28)	1.00 to 3.00	-10.00 to +6.00
	Transitions (FT-35)	.75 to 4.00	-6.00 to +6.00
1.56	Clear (FT-28)	1.00 to 3.50	-10.00 to +7.00
	Clear (FT-35)	1.00 to 3.00	-10.00 to +7.00
	SunSensors	1.00 to 3.00	-10.00 to +6.50
	BluTech (FT-28 only) High Impact Indoor/Outdoor	1.00 to 3.50	-7.00 to +6.00
1.586 Poly	Life Rx Poly (FT-28 only)	1.00 to 3.00	-10.00 to +4.50
	Signia Poly	1.00 to 3.00	-9.50 to +6.00
TRIFOCAL 7X28			
1.50	Signia 1.50	1.50 to 3.00	-5.00 to +6.00
1.50	Transitions, PhotoViews	1.50 to 3.00	-5.00 to +6.00
1.56	Clear, SunSensors	1.50 to 3.00	-9.50 to +6.50
1.586 Poly	Life Rx Poly	1.50 to 3.00	-10.00 to +4.50
	Signia Poly	1.50 to 3.00	-9.50 to +6.00
TRIFOCAL 8X35			
1.50	Signia 1.50	1.50 to 3.00	-5.00 to +6.00

RX PRISM IS AVAILABLE ON ALL PROGRESSIVE LENS DESIGNS. The maximum amount of prism or combination of prism is 5.00 diopters in any direction.
Diameter - The minimum uncut diameter offered is 60mm; the maximum is dependent on blank availability. Lenses are cribbed to the nearest value at least 1mm greater than the final shape in 2.5mm steps.