

**PROGRESSIVE LENS TECHNICAL SUMMARY**

Semi-Finished Progressive Lenses	Vision Council Lens Specifications				Drop	Inset	Corridor Lengths	Min. Fit Height
	LRP In	LRP Down	PRP Out	PRP Up				
KODAK Precise® Lenses	3.0	-4.0	0.0	-4.0	4.0	3.0	17mm	17mm
KODAK Precise Short Lenses	3.0	-4.0	0.0	-4.0	4.0	3.0	13mm	13mm

**Add Range: +1.00 to +3.00 in 0.25 D steps / \*+0.75 to 3.50 in 0.25 D steps**



Freeform Progressive Lenses	Vision Council Lens Specifications				Drop	Inset	Corridor Lengths	Min. Fit Height
	LRP In	LRP Down	PRP Out	PRP Up				
KODAK Unique DRO® /DRO HD Lenses	3.0	-4.0	0.0	-4.0	4.0	Variable	13, 14, 15, 16, 17, 18mm	13mm
KODAK Unique™ /HD Lenses	3.0	-4.0	0.0	-4.0	4.0	Variable	13, 14, 15, 16, 17, 18mm	13mm
KODAK Precise® Plus Lens	3.0	-4.0	0.0	-4.0	4.0	3.0	13mm	13mm
KODAK Precise Short Plus Lens	3.0	-4.0	0.0	-4.0	4.0	3.0	17mm	17mm
KODAK Precise PB Lenses	3.0	-4.0	0.0	-4.0	4.0	3.0	17mm	17mm
KODAK Precise Short PB Lenses	3.0	-4.0	0.0	-4.0	4.0	3.0	13mm	13mm
KODAK Easy / 18mm	3.0	-4.0	0.0	-4.0	4.0	3.0	18mm	18mm
KODAK Easy / 14mm	3.0	-4.0	0.0	-4.0	4.0	3.0	14mm	14mm
KODAK SoftWear™ Lenses* (Computer) <i>(previously KODAK MonitorView™ Lenses)</i>	3.0	-2.0	0.0	-2.0	2.0	3.0	14mm	17mm

**Add Range: +0.75 to +3.50 in .25 D steps**

*\*KODAK SoftWear Lenses are not progressive lenses and devote most of the viewing to the near and intermediate distances.*

NOTES: The inset is the horizontal decentration of the lens design. (The distance from the geometric center of the lens blank to the prism reference point.)  
Corridor length is the distance in millimeters from the fitting cross to the full add power.  
The fitting or seg height is the measurement from the fitting cross to the lowest bottom edge of the lens (Must consider lens shape i.e. right triangle).  
The drop is the distance (mm) from the center of the fitting cross to the PRP.